


CEE Angled plugs




Angled plug IP44 TWIST

	16 Amp			32 Amp		
Poles	3	4	5	3	4	5
a [mm]	96	98	108	127	127	135
b [mm]	59	62	71	82	82	90
c [mm]	47	53	61	63	63	70
d [mm]	82	87	99	111	111	114
e [°]	15	15	20	25	25	25
K cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Wire flexible [mm²]	1-2,5			2,5-6		
Contact screws [Ncm]	100			110		
SW [mm]	38	38	42	50	50	50
Weight [g]	107	130	155	174	194	236

- with screw terminals
- housing material
16/3 16/4: PA6
16/5 32/3 32/4 32/5: PC/ABS
- contacts: brass
 - to order nickel-plated contacts please add a "v" e.g. 8015-6v

IP44 splashproof




Angled plug IP44 TWIST TT

	16 Amp			32 Amp		
Poles	3	4	5	3	4	5
a [mm]	96	98	108	127	127	135
b [mm]	59	62	71	82	82	90
c [mm]	47	53	61	63	63	70
d [mm]	82	87	99	111	111	114
e [°]	15	15	20	25	25	25
K cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Wire flexible [mm²]	1-2,5			2,5-6		
SW [mm]	38	38	42	50	50	50
Weight [g]	110	134	160	179	199	244

- screwless connection technology
- housing material
16/3 16/4: PA6
16/5 32/3 32/4 32/5: PC/ABS
- contacts: brass
 - to order nickel-plated contacts please add a "v" e.g. 8015-6TTv

IP44 splashproof




Angled plug IP67 TWIST

	16 Amp			32 Amp		
Poles	3	4	5	3	4	5
a [mm]	96	98	108	127	127	135
b [mm]	71	79	87	93	93	100
c [mm]	82	87	99	111	111	114
d [°]	15	15	20	25	25	25
K cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Wire flexible [mm²]	1-2,5			2,5-6		
Contact screws [Ncm]	100			110		
SW [mm]	38	38	42	50	50	50
Weight [g]	128	155	186	215	234	278

- with screw terminals
- housing material
16/3 16/4: PA6
16/5 32/3 32/4 32/5: PC/ABS
- contacts: brass
 - to order nickel-plated contacts please add a "v" e.g. 80152-6v

IP67 watertight



Angled plug IP67 TWIST TT

	16 Amp			32 Amp		
Poles	3	4	5	3	4	5
a [mm]	96	98	108	127	127	135
b [mm]	71	79	87	93	93	100
c [mm]	82	87	99	111	111	114
d [°]	15	15	20	25	25	25
K cable Ø [mm]	6-15	6-15	8-16	11,5-20	11,5-20	11,5-22
Wire flexible [mm²]	1-2,5			2,5-6		
SW [mm]	38	38	42	50	50	50
Weight [g]	130	158	191	219	238	288

- screwless connection technology
- housing material
16/3 16/4: PA6
16/5 32/3 32/4 32/5: PC/ABS
- contacts: brass
 - to order nickel-plated contacts please add a "v" e.g. 80152-6TTv

IP67 watertight

Amp.	Poles	pack. unit	110V~	230V~	400V~	500V~	>50-500V~	>50-500V~
			50/60Hz 4h	50/60Hz 3p=6h 4p+5p=9h	50/60Hz 3p=9h 4p+5p=6h	50/60Hz 7h	100-300Hz 10h	301-500Hz 2h
			Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.
16	3	10	8013-4	8013-6	8013-9	8013-7	8013-10	8013-2
16	4	10	8014-4	8014-9	8014-6	8014-7	8014-10	8014-2
16	5	10	8015-4	8015-9	8015-6	8015-7	8015-10	8015-2
32	3	10	8023-4	8023-6	8023-9	8023-7	8023-10	8023-2
32	4	10	8024-4	8024-9	8024-6	8024-7	8024-10	8024-2
32	5	10	8025-4	8025-9	8025-6	8025-7	8025-10	8025-2



8013-6

16	3	10	8013-4TT	8013-6TT	8013-9TT
16	4	10	8014-4TT	8014-9TT	8014-6TT
16	5	10	8015-4TT	8015-9TT	8015-6TT
32	3	10	8023-4TT	8023-6TT	8023-9TT
32	4	10	8024-4TT	8024-9TT	8024-6TT
32	5	10	8025-4TT	8025-9TT	8025-6TT



8013-6TT

16	3	10	80132-4	80132-6	80132-9	80132-7	80132-10	80132-2
16	4	10	80142-4	80142-9	80142-6	80142-7	80142-10	80142-2
16	5	10	80152-4	80152-9	80152-6	80152-7	80152-10	80152-2
32	3	10	80232-4	80232-6	80232-9	80232-7	80232-10	80232-2
32	4	10	80242-4	80242-9	80242-6	80242-7	80242-10	80242-2
32	5	10	80252-4	80252-9	80252-6	80252-7	80252-10	80252-2



80142-6

16	3	10	80132-4TT	80132-6TT	80132-9TT
16	4	10	80142-4TT	80142-9TT	80142-6TT
16	5	10	80152-4TT	80152-9TT	80152-6TT
32	3	10	80232-4TT	80232-6TT	80232-9TT
32	4	10	80242-4TT	80242-9TT	80242-6TT
32	5	10	80252-4TT	80252-9TT	80252-6TT



80142-6TT

