

## **EOS4 3B AH**

Order Code: 1310651

Access Control Safety Light Curtain with Automatic Restart. Extended Range



**Safety level**

Type 4 - PL e

**Protected height (mm)**

810

**Resolution (mm)**

Multi-beams

**Max. range (m)**

20

**Restart**

Automatic

**Functioning system**

Emitter / Receiver

## **Technical Description**

Compact Safety Light Curtain: Type 4, SIL 3, SILCL 3, PL e, Cat. 4

Cross Section: 28 x 30 mm

No blind area on one side

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

## Features

Safety level	Type 4 - PL e
Protected height (mm)	810
Resolution (mm)	Multi-beams
Controlled height (mm)	890
Max. range (m)	20
Restart	Automatic
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 4 - SIL 3 - SILCL 3 - PL e - Cat. 4
Operating temperature (°C)	- 20 ... 55
Response time (ms)	2,5
Number of beams	3
Max. length of the connection cables (m)	100
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (400 mA at 24 VDC) with protection against short circuit, overload and reverse polarity
Connections	M12 5-pole connectors
MTTFD (ISO13849) years	538,8
Safety outputs	2 OSSD PNP (400 mA at 24 VDC)
Safety functions	With external module
Detection	Access control
Packaging dimensions HxLxW (mm)	145 x 1010 x 200

## EOS4 3B AH

Product class	B
Custom tariff	85365019


## Electrical data

Power supply (VDC)	24 ± 20%
--------------------	----------

## Mechanical data

Overall height (mm)	953
Cross section dimensions (mm)	28 x 30
Degree of protection	IP65 - IP67
Fastening	Back slot with set of LE type brackets (included) or to the top and lower end with swivel brackets SFB E (optional)
Gross weight (g)	3061,66

Technical drawings



**Certificates**

